

TECHNICAL DATASHEET FOR FERROUS/NON-FERROUS TOWERPACKINGS (RINGS)

PALL RINGS

	Guage	No. of pieces per M ³ ±10%	Weight per M ³ in Kgs ±10%	Surface area M ² /M ³ ±10%	% Free space
12 mm	22	370968	1393	488	72
	24	374251	1092	491	73
	26	377534	878	495	74
15 mm	22	233510	1378	483	76
	24	234746	1076	485	78
	26	235981	865	488	79
20 mm	22	107436	1128	392	77
	24	108336	881	396	78
	26	109236	707	399	79
25 mm	22	45325	740	258	84
	24	45713	580	261	85
	26	46101	466	263	86
35 mm	22	14120	452	158	90
	24	14226	354	159	91
	26	13908	692	156	92
50 mm	22	5930	602	135	93
	24	6036	394	138	94
	26	6070	490	139	94

TECHNICAL DATASHEET FOR FERROUS/NON-FERROUS TOWERPACKINGS (RINGS)**RASCHIG RINGS**

Size	Guage	No. of pieces per M³ ±10%	Weight per M³ in Kgs ±10%	Surface area M²/M³ ±10%	% Free space
12 mm	22	398890	1135	397	77
	24	402420	891	400	78
	26	405950	716	404	79
15 mm	22	251423	1110	392	80
	24	252747	879	395	80
	26	254071	704	397	80
20 mm	22	115519	917	320	82
	24	116490	719	323	82
	26	117461	577	326	83
25 mm	22	48749	600	210	86
	24	49173	472	212	86
	26	49597	379	214	87
35 mm	22	14826	557	125	90
	24	15037	365	128	92
	26	15143	286	128	93
50 mm	22	6534	489	113	92
	24	6612	323	114	93
	26	6647	256	115	93
75 mm	28	1871	325	73	95