



**C1, Private Industrial Estate,
Pollachi Main Road,
Coimbatore-641021**

**Contact:
+91 9080759716
+91 8754928514**

Tower Packings

Tower packings are manufactured in a range of materials to meet diverse operating conditions across chemical, petrochemical, environmental and gas-treatment industries. Each material category offers a unique balance of chemical resistance, temperature capability, mechanical strength and cost efficiency. The selection of packing material is therefore governed by process parameters such as operating temperature, corrosive media, mechanical load, fouling tendency and overall lifecycle requirements.

Ceramic Tower Packings

Ceramic packings are preferred in high-temperature and strongly corrosive environments where metallic and polymeric materials cannot be used. They offer excellent acid resistance, thermal stability, and dimensional integrity under continuous heat exposure. Ceramic packings are widely used in sulfuric acid plants, fertilizer units, chlorination towers, and scrubbing systems handling hot or reactive gas streams.

Hi-Polymer (Plastic) Tower Packings

High-performance polymer packings—typically PP, PVDF, PTFE or other engineering plastics—provide low weight, low pressure drop, and excellent resistance to a wide range of chemicals. They are particularly suited for low to medium temperature operations, biological treatment systems, and corrosive aqueous media where metal packings would degrade. Their high surface-area-to-weight ratio and easy installation make them economical for large-diameter towers.

Graphite Tower Packings

Graphite packings deliver exceptional thermal shock resistance and outstanding corrosion resistance, especially in highly oxidative or aggressively acidic environments. They maintain structural stability at elevated temperatures and are commonly used in processes involving phosphoric acid, bromine, chlorination gases, and specialty chemical applications requiring both temperature and corrosion resilience beyond typical metallic ranges.

Carbon Tower Packings

Carbon-based packings offer good chemical inertness, moderate high-temperature capability, and low density. They are suited for applications involving halogenated compounds, organics, and systems requiring minimal contamination. Carbon is advantageous where weight reduction and chemical purity are critical, though it is less resistant to oxidation at high temperatures compared to graphite.

Ferrous Metal Tower Packings

Packings manufactured from carbon steel or stainless steel provide high mechanical strength, durability and impact resistance. They are suitable for high-pressure or mechanically demanding services and are typically used in refinery towers, distillation units, and systems involving non-acidic process streams. Stainless steels extend corrosion resistance, but their performance is still limited in strong acids or chlorinated environments.

Non-Ferrous Metal Tower Packings

Non-ferrous alloys such as copper, aluminum, nickel-based alloys and duplex materials are selected for their specific corrosion-resistance profiles, thermal conductivity and mechanical performance. These packings are used in specialized heat-transfer applications, gas drying systems, and processes where both chemical compatibility and superior metal properties are required compared to ferrous alternatives.

Overall, the choice of tower packing material is driven by a balance of chemical environment, temperature range, operational reliability, and cost considerations. Understanding the strengths of each material class allows engineers to select the most efficient and durable packing for their specific process conditions.

Material	Temperature Limit	Corrosion Resistance	Typical Applications	Estimated Cost Range
Ceramic	Up to 1000–1500 °C (composition dependent)	Excellent (acids, hot gases, solvents)	High-temp absorbers, sulfuric acid plants, drying towers, chlorination systems	\$\$ – \$\$\$
Hi-Polymer (PP, PVDF, PTFE, etc.)	90–260 °C depending on polymer	Excellent for acids/alkalis; limited oxidizer resistance	Low/medium temp scrubbers, wastewater and biological treatment	\$ – \$\$
Graphite	400–800 °C (higher in inert env.)	Exceptional (strong acids, halogens); limited oxidation resistance	Phosphoric acid, chlorine/bromine systems, aggressive corrosion	\$\$\$ – \$\$\$\$
Carbon	300–500 °C (non-oxidizing)	High inertness; moderate acid/alkali resistance	Organic processing, halogenated streams, inert packing needs	\$\$ – \$\$\$
Ferrous Metals (CS, SS)	300–600 °C depending on grade	Good for general chem services; SS resists mild acids/alkalis	Distillation towers, refinery services, non-acid streams	\$\$ – \$\$\$
Non-Ferrous Metals (Cu, Al, Ni alloys)	200–700 °C alloy dependent	Very good for specific corrosive chemistries; alloy dependent	Heat-transfer towers, drying columns, niche chem processes	\$\$\$ – \$\$\$\$